# Blackline SI5<sup>+</sup>


# Compact, vented sub-bass system

#### features

- Compact vented sub-bass
- Direct radiating 15" (380mm) driver
- High temperature 4" (100mm) voice coil
- Top hat fitting for pole mounting F12<sup>+</sup>/F15<sup>+</sup>
- Five year limited warranty

### applications


- Club sound reinforcement
- Theatre sub-bass
- AV presentations



The  $$15^+$$  is provided with a top hat fitting that can be used to pole mount an  $$F10^+$$  or  $$F12^+$$  above the enclosure.

496mm

#### overall dimensions





## technical specifications

TYPE	Compact, vented sub-bass system
FREQUENCY RESPONSE (I)	$45Hz-120Hz \pm 3dB$
	-10dB @ 40Hz
DRIVERS	15" (380mm)/4" (100mm) voice coil LF driver
RATED POWER (2)	750W AES, 3000W peak
RECOMMENDED AMPLIFIER	600W-1500W into 4 ohms
SENSITIVITY (3)	101dB (half space)
MAXIMUM SPL (4)	129.5dB continuous, 135.5dB peak (half space)
NOMINAL IMPEDANCE	8 ohms
DISPERSION (-6dB)	
CROSSOVER	120Hz active/passive low pass filter
ENCLOSURE	100 litre, multi-laminate birch ply
FINISH	Textured black paint
PROTECTIVE GRILLE	Black perforated steel
CONNECTORS	2 x Neutrik NL4
PIN CONNECTIONS	LF+,-: I+,I-, Link thro': 2+,2-
FITTINGS	I x mounting pole socket
	2 x pocket handles
DIMENSIONS	(W) 470mm x (H) 690mm x (D) 496mm
	(W) 18.5ins x (H) 27.2ins x (D) 19.5ins
WEIGHT	38.5kg (84.5lbs)
	<del>-</del> ', '

Century Point, Halifax Road, Cressex Business Park,
High Wycombe, Buckinghamshire HPI2 3SL, England.
Telephone: +44 (0)1494 53531 Facsimile: +44 (0)1494 438669
E-mail: info@martin-audio.com
All information is Copyright © 2007 Martin Audio Ltd.

